




Status of the VEPP-2000 Collider Project

Yuri Shatunov

*Budker Institute of Nuclear Physics,
630090, Novosibirsk, Russia*

Frascati, September 2003

Layout of the VEPP(-2M)-2000 collider complex



- ◆ $E \approx 1 \text{ GeV}$ (per beam)
- ◆ $L \approx 1 \times 10^{32} \text{ cm}^{-2} \text{ sec}^{-1}$ (1x1 bunch)

ВЭПП-2000

TASKS for VEPP-2000:

1. To study “peculiarities” above 1.4 GeV (total).
2. To measure with good enough precision total hadron cross-section in 1.4 - 2 GeV (total) - for hadron contribution to muon g-2.
3. To measure form-factors (in time-like region) for protons and neutrons

$$e^+ + e^- \longrightarrow p + \text{anti-}p ; \quad e^+ + e^- \longrightarrow n + \text{anti-}n .$$

4. For accelerator physics: “Round Beams”!

Increasing the Luminosity

- ❑ Number of bunches
- ❑ Bunch-by-bunch luminosity

$$L = \frac{\pi\gamma^2\xi_x\xi_y\epsilon_x f}{r_e^2\beta_y^*} \left(1 + \frac{\sigma_y}{\sigma_x}\right)^2$$

Round Beam:

- ✓ Geometric factor
- ✓ Beam-beam limit enhancement



Concept of Round Beams


Conservation of the z-component
of angular momentum $M_z = yp_x - xp_y$

Requirements:

- ✓ Round cross-section of beams at IP
- ✓ Machine optics has rotational symmetry

4×4 transfer matrix

$$T = \begin{pmatrix} A & -B \\ B & A \end{pmatrix}$$




Motion in central field with additional integral of motion
reduces the transverse oscillations from 2D to 1D!

(V.V.Danilov et al, Frascati Physics
Series Vol. X (1998), p.321)


Practical Realization of Round Beams: Options for VEPP-2000

$$\int_0^l H_{sol} ds = \frac{1}{2} \oint H_z ds$$



Practical Realization of Round Beams


Conversion of conventional machine using beam adapters




(A.Burov, S.Nagaitsev, Ya.Derbenev, FERMILAB-Pub-01/060-T)




View of the Collider



Lattice




Weak-Strong Beam-Beam Simulation



Emittance of the weak beam vs. the beam-beam parameter. Sextupoles off. 1,2 – two codes.




Weak-Strong Beam-Beam Simulation



Emittance of the weak beam vs. the beam-beam parameter. Sextupoles on. 1,2 – two codes.




Strong-Strong Beam-Beam Simulation



Macroparticles/bunch $N_p = 50000$, transverse mesh 128×128 ;
Field calculated via FFT
(K.Ohmi, Phys. Rev. E **59**, 7287 (2000))




Strong-Strong Beam-Beam Simulation



Beam size and luminosity vs. the nominal beam-beam parameter (PAC'2003)



Strong-Strong Beam-Beam Simulation



Comparison of the sextupoles on and off options.




Main Parameters of VEPP-2000


Parameter	Value
Circumference	24.38 m
RF frequency	172 MHz
RF voltage	100 kV
RF harmonic	14
Momentum compaction	0.036
Synchrotron tune	0.0035
Energy spread	6.4×10^{-4}
Beam emittances (x,y)	1.29×10^{-7} m rad
Dimensionless damping decrements (x,y,z)	2.19×10^{-5} , 2.19×10^{-5} , 4.83×10^{-5}
Betatron tunes	4.05, 2.05
Betatron functions @ IP	10 cm
Particles per bunch	1×10^{11}
Beam-beam parameter (x,y)	0.075, 0.075
Luminosity per IP (at 1GeV)	$1 \times 10^{32} \text{ cm}^{-2} \text{ s}^{-1}$




Dipole Magnet (2.4 T)




Dipole: Magnetic Measurements



Dipole: Magnetic Measurements



Guiding field 0.6 T



Guiding field 2.38 T




31.10.02




31. 10. 2002



Quadrupole





Quadrupole: Magnetic Measurements





Vacuum Chamber



Single-Mode RF Cavity (172 MHz)




Calculated main mode & HOM



RF cavity parts



Solenoid 13.0 T



Solenoid: Coils



Nb-Sn



Nb-Ti


13.08.01




Assembly of the Nb-Ti and Nb-Sn coils



VEPP-2000 Luminosity



POSITRON SOURCE



hall of 300 @ 500 MeV linacs



510 MeV damping ring



21.08.03



Summary

- ♠ Start of VEPP-2000 construction – January 2000
- ♠ Dipole, quads, sextupoles, skew-quads, steering coils, 6 from 8 vacuum chamber are ready, tested and installed
- ♠ 13 T field is achieved in solenoid prototype
- ♠ Weak-strong and strong-strong simulation show high ξ for the round beams
- ♠ Construction of transfer line from e^+ source is going on
- ♠ Beam → at the end of 2004

